

FDN20

HIGH PERFORMANCE NEAR EDGE WAX RESIN

PERFORMANCE CHARACTERISTICS

- Prints on most types of packaging films
- Prints on all types of coated papers and synthetic films
- Prints black, bold and crisp text, graphics and barcodes
- Excellent scratch and smudge resistance
- Excellent print quality at speeds up to 500 mm/sec
- Excellent print definition for clean, durable and dense barcodes
- ISEGA certification
- Easy slot-in product replacement for other wax resin grades

Near Edge Technology Grades*

FDN20	High Performance Wax Resin Very versatile for all types of labels and packaging films
FDN21	High Performance Wax Resin Coated on 4.0-micron film for longer length ribbons
FDN22	Specialty Wax Resin For extra durability and higher print speeds
FDN30	Specialty Resin Extra durability to heat and abrasion with high print speeds

*These ribbon grades are for use with near edge technology printers. We also offer ribbons grades for flat head technology printers and thermal transfer coders.

FDN20

HIGH PERFORMANCE NEAR EDGE WAX RESIN

RIBBON SPECIFICATIONS	
DESCRIPTION	TECHNICAL
BASE FILM CARRIER	4.5 Micron Polyester
TOTAL RIBBON THICKNESS	7.0 Microns +/- 0.02
INK TYPE	Wax/Resin (near edge technology)
COLOUR	Black
INK MELTING POINT	70°C
DENSITY	1.8

RIBBON STORAGE CONDITIONS	
DESCRIPTION	TECHNICAL
TEMPERATURE	5°C to 35°C (41F to 95F)
HUMIDITY	10% to 85% relative humidity
LIGHT	Avoid direct sunlight

CERTIFICATIONS AND APPROVALS	
DESCRIPTION	TECHNICAL
ISO 9001:2015 & ISO 14001:2015	All ribbons have been manufactured to these international quality standard
RoHs/WEEE	EC directives 2012/19/EU and 2011/65/EU, compliance to the limitation of dangerous substances in electrical and electronics equipment
HEAVY METALS	94/62/EC & 2011/65/EU
TSCA/CP 65	The ribbon does not contain any of the substances on this list
AMES TEST	The ribbon is not mutagenic, does not cause DNA modifications
EC DIRECTIVES	1999/45/EC and 2001/59/EC. This ribbon does not contain any substance classified as dangerous for health
FOOD CONTACT	1935/2004/EC
REACH/SVHC	Does not contain any of the SVHCs listed - 1907 / 2006/EC
DISPOSAL	To be disposed of as mixed industrial waste

This information is the best available on the above ribbon grade. These results should, however, only be regarded as a general guide to material properties and is not a guarantee.



JS Etiketten und Barcodesysteme

Kirchweg 4a
64390 Erzhausen
Germany
T: +49 (0)6150 5421885
E: verkauf@farbband-discount.de